


气凝胶绝热毡 FMC200

Aerogel Blanket FMC200



Specification

产品规格

厚度 Thickness	FMC200-3	3mm
	FMC200-6	6mm
	FMC200-10	10mm
长度 Length	FMC200-3	34m
	FMC200-6	34m
	FMC200-10	25m
宽度 Width	1500mm	
颜色 Color	白色或银白色 White or Silver White	
推荐使用温度 Suggested Working Temperature	-200~100℃	
说明: 可根据客户要求定制。 Notes: Sizes could be on customers' requirement.		

性能参数 Technical Data	尺寸稳定性 Size Stability	1%	GB/T 8811	
	压缩性能 Compressive Property	@10% 50KPa	GB/T 13480	
		@20% 100KPa		
	燃烧等级 Fire Rating	A1	GB/T 5460	
	拉伸强度 Tensile Strength	GB/T 17911		
	导热系数 Thermal Conductivity	25℃	0.020	GB/T 10295
		-200℃	0.009	
		-150℃	0.010	
		-100℃	0.011	
		-50℃	0.014	
	100℃	0.022		
用途 Function	-200℃至室温的管道设备保冷 For -200℃ to room temperature pipes and equipment cold insulation			
应用领域 Application	化工、生物医药管道设备保冷、液氮、LNG等管道设备保冷 For chemical, biological medicine pipes and equipment, liquid nitrogen, LNG ect. pipes and equipment cold insulation			